

- please check option/version
 standard & recommended version
 included, no choice
 option not available

BMT 964

BMT 964 BT

BMT 964 C

BMT 964 AQ

BMT 964 AQ
- INLINE

Basic model	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Concentration range ¹⁾					
2 g/Nm ³ (or 0.15 %wt/wt)	<input type="checkbox"/>	2)	2)	—	—
5 g/Nm ³ (or 0.35 %wt/wt)	<input type="checkbox"/>	2)	2)	—	—
10 g/Nm ³ (or 0.7 %wt/wt)	<input type="checkbox"/>				10 g/m ³ (ppm)
20 g/Nm ³ (or 1.5 %wt/wt)	<input type="checkbox"/>				—
50 g/Nm ³ (or 3.5 %wt/wt)	<input type="checkbox"/>				50 g/m ³ (ppm)
100 g/Nm ³ (or 7 %wt/wt)	<input type="checkbox"/>				100 g/m ³ (ppm)
150 g/Nm ³	<input type="checkbox"/>	—	—	—	150 g/m ³ (ppm)
200 g/Nm ³ (or 14 %wt/wt)	<input type="checkbox"/>				—
300 g/Nm ³ (or 20 %wt/wt)	<input type="checkbox"/>				—
400 g/Nm ³ (or 26 %wt/wt)	<input type="checkbox"/>				—
					■ 100 g/m ³ (ppm)
					contact factory
Pressure range					
standard, 1.15 bara	<input type="checkbox"/>	●	●	■	—
high, 1.50 bara	<input type="checkbox"/>			—	—
high, 2.00 bara	<input type="checkbox"/>			—	—
high, 2.50 bara	<input type="checkbox"/>			—	—
high, 3.00 bara	<input type="checkbox"/>			—	—
high, 3.50 bara	<input type="checkbox"/>			—	—
high, 4.00 bara	<input type="checkbox"/>			—	—
higher ranges on request	<input type="checkbox"/>			—	—
Fittings					
for 3 x 5mm PTFE	<input type="checkbox"/>	●	●	●	—
for 4 x 6 mm PTFE	<input type="checkbox"/>		—		—
1/8" Swagelok	<input type="checkbox"/>				—
1/4" Swagelok	<input type="checkbox"/>		—		—
6mm Swagelok	<input type="checkbox"/>		—		—
Other built-in options					
option Dirt Trap (Cabinet)	<input type="checkbox"/>	—	—		—
option Internal Purge Unit	<input type="checkbox"/>	1.15 bara only	1.15 bara only	■	—
Sensor Version (for RD)	<input type="checkbox"/>		—	—	—

Choosing a model and its ranges (concentration and pressure) is mandatory!

OZONE-IN-OFF-GAS SYSTEM: contact factory for options

Note 1): The ranges in %wt/wt are not equal to the ranges in g/Nm³ - the unit may be switched by the user at any time.

Note 2): For ranges 2 and 5g/Nm³, the standard instrument is double in height (144 x 144mm).

Note 3): An internal purge unit is only available for a pressure range of 1.15 bara, in general.

Note 4): LET-LOK fitting, Swagelok interchangeable

To find out more about the above models and their options, please refer to our data sheets (<http://www.bmt-berlin.de>).